

HI-TECH DURAVENT

Flexible Hose & Ducting

ULD



TEMPERATURE RANGE: -65°F to 200°F

CONSTRUCTION: Polyurethane reinforced with a bronzed wire helix.

STANDARD COLORS: Clear

STANDARD LENGTHS: 25', 50'

DESCRIPTION: ULD is a lightweight, ultra-flexible urethane duct for general purpose use where abrasion resistance and flexibility are required. The clear material makes it easy to locate blockages, and the lightweight construction makes it easy to manipulate. ULD is the perfect choice for a variety of applications, from hand-held use up to semi or fully automated machinery.

FEATURES/BENEFITS:

- Abrasion Resistant
- Highly Flexible
- Lightweight
- Highly compressible
- Transparent for easy locating of blockages
- Perfect for applications with constant movement & flexing
- High Temperature Resistance
- Moisture Resistant
- UV/Ozone Resistant
- Made with FDA Compliant Materials

APPLICATIONS:

- Material Handling
- Chip Collection
- Dust Collection
- Chemical Fume Evacuation
- General Purpose Fume Evacuation
- Oil Mist Collection
- Air Movement/Handling

INDUSTRIES:

- Woodworking
- Lawn/Leaf
- Metal Fabrication
- Insulation Blowing/Removal
- Powder Paint Recovery
- Food/Beverage

ID (in)	WORKING PRESSURE (psi)	VACUUM RATING (inHg)	BEND RADIUS (in)	COMPRESSION RATIO	OD (in)	WALL THICKNESS	WEIGHT (lb/ft)
2	14	10	1.6	2.5:1	2.2	0.015	0.172
2.5	12	9	1.8	2.5:1	2.75	0.015	0.2
3	10	7	2	3:1	3.25	0.015	0.228
4	7	5	2.3	3.5:1	4.25	0.015	0.375
5	6	4	2.6	3.5:1	5.25	0.015	0.488
6	6	3	3	3.5:1	6.25	0.015	0.6

ABRASION-RESISTANT

UV/OZONE-RESISTANT

ULTRA-FLEXIBLE

MOISTURE-RESISTANT

LIGHTWEIGHT

FDA/FOOD SAFE





Flexible Hose & Ducting

528 Carwellyn Road
Abbeville, SC 29620

1177 Markley Drive
Plymouth, IN 46563

615 South 56th Avenue
Phoenix, AZ 85043

4610 Eastgate Parkway, Unit 3
Mississauga, Ontario
Canada L4W 3W6

For more information visit www.hitechduravent.com
Call us at 800.348.6500 (USA) | 800.263.3359 (CANADA)
Fax us at 800.348.6599
Email us at sales@hitechduravent.com