

RFH

Physical Characteristics, Pressure & Flex Values

ID	Working Pressure	Vacuum	CL Bend Radius	Compress Ratio	OD Nominal	Wall Thickness	Weight
(in.)	(psi)	(inHg)	(in.)		(in.)	(in.)	(lbs./ft.)
1.25	28	>29	1.50	1ft/6in	1.49	.026	.11
1.50	24	>29	1.75	1ft/6in	1.75	.026	.22
1.75	22	>29	2.00	1ft/9in	2.00	.026	.23
2.00	17	>29	3.50	1ft/6in	2.27	.030	.24
2.50	13	28	4.00	1ft/6in	2.77	.030	.29
3.00	10	28	4.25	1ft/5in	3.27	.030	.32
3.50	10	20	5.25	1ft/6in	3.77	.030	.41
4.00	10	25	6.50	1ft/6in	4.29	.030	.50
5.00	9	15	8.00	1ft/6in	5.29	.030	.63
6.00	8	11.5	8.75	1ft/6in	6.29	.030	.85
7.00	7	10	10.50	1ft/7in	7.35	.030	.95
8.00	6	5.5	12.00	1ft/7in	8.35	.030	1.20
10.00	4	5	12.50	1ft/4in	10.38	.030	1.63
12.00	4	4	13.75	1ft/4in	12.38	.030	1.90
14.00	2	2	18.00	1ft/4in	14.48	.030	1.87
16.00	2	2	21.00	1ft/4in	16.48	.030	3.19
18.00	2	2	21.50	1ft/4in	18.48	.030	3.36
20.00	1	2	25.50	1ft/4in	20.50	.030	3.63
24.00	1	1	36.00	1ft/4in	24.50	.030	3.81

Pressure and Vacuum data based on straight lengths of hose at ambient temperature 72° F.

Construction:	Thermoplastic rubber reinforced with a wire helix
Temperature range:	-60° F to 275° F (intermittent to 300° F)
Standard color:	Black
Standard lengths:	25', 50'

www.hitechduravent.com

smiths

528 Carwellyn Road, Abbeville, SC 29620 • 1177 Markley Drive, Plymouth, IN 46563 • Tel: 800-348-6500
4610 Eastgate Parkway, Unit 3, Mississauga, Ontario, Canada L4W 3W6 • Tel: 905-602-9660 • Fax: 800-348-6599